

Safety Data Sheet

REVISION: February 2017
Supersedes: May 2016 version



Section 1 Identification of the substance/mixture and of the Company/undertaking

- 1.1 Product Identifier**
- | | |
|----------------------------|--|
| Chemical name | Boric acid |
| CAS No: | 10043-35-3 |
| REACH Registration Number: | 01-2119486683-25-0000 |
| EC No: | 233-139-2 |
| Synonyms: | Boric acid, Orthoboric acid, Boracic acid |
| Product Names: | Optibor SP, Optibor EP, Optibor HP, Optibor TG, Optibor TP, Optibor SQ |
| Grades: | All |
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
- Identified Uses:**
- Binding agent
 - Chemical production
 - Complexing agent
 - Corrosion inhibitors and anti-scaling agents
 - Fertilisers
 - Flame retardants
 - Flux agents for casting
 - Intermediate
 - Laboratory chemicals
 - Lubricants and lubricant additives
 - Oxidising agents
 - Photosensitive agents and other photo-chemicals
 - pH-regulating agents
 - Plating agents and metal surface treating agents
 - Process regulator (other than polymerisation or vulcanization processes)
 - Process regulator (used in polymerisation or vulcanization processes)
 - Processing aid not otherwise listed
 - Stabilisers
 - Surface active agents
 - Viscosity modifiers
- A complete list of uses is provided in the introduction to Annex – Exposure Scenarios*
- Uses advised against:** Consumer uses above the specific concentration limit.
- 1.3 Details of the supplier of the SDS**
- | | |
|-------------------|--|
| Company Name: | Borax Europe Limited |
| Address: | 6 St. James's Square
London, SW1Y 4AD
United Kingdom |
| Telephone number: | +44 (0)20 7781 2000 |
| Email: | rtm.msds@riotinto.com |
- 1.4 Emergency telephone number:** +44 (0) 1235 239 670
Official advisory body telephone number: None

Section 2 Hazards identification

2.1 Classification of the substance or mixture

Classification (CLP Regulation (EC) No 1272/2008): Classified as toxic for reproduction (Repr. 1B; H360FD)

Boric acid has a specific concentration limit of $\geq 5.5\%$ for toxic for reproduction classification.

Classification (Directive 67/548/EEC): Classified as toxic for reproduction (Repr. Cat 2; R60-61)

Boric acid has a specific concentration limit of $\geq 5.5\%$ for toxic for reproduction classification.

Refer to Section 16 for the full text of Hazard Statements and R-phrases mentioned above.

2.2 Label Elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Hazard Pictograms



Signal word: Danger

Hazard statements:

H360FD: May damage fertility. May damage the unborn child.

Precautionary statements:

P202: Do not handle until all safety precautions have been read and understood.

P281: Use personal protective equipment as required.

P308+P313: IF exposed or concerned: Get medical advice.

P501: Dispose of contents/container in accordance with local regulation.

Supplemental Information

Restricted to professional users.

2.3 Other Hazards

H303: May be harmful if swallowed.

Section 3 Composition/information on ingredients

3.1 Substances

Chemical Name	CAS#	EC#	% content	Classification (1272/2008/EC)	Classification (67/548/EEC)
Boric acid	10043-35-3	233-139-2	>99.9	Repr. 1B; H360FD	Repr. Cat 2; R60-61

Refer to Section 16 for the full text of Hazard Statements and R-phrases mentioned above.

Section 4 First aid measures

4.1 Description of First aid measures

Protection of first-aiders: No special protective clothing is required.

Inhalation: If symptoms such as nose or throat irritation are observed, remove to fresh air.

Eye contact: Use eye wash fountain or fresh water to cleanse eye. If irritation persists for more than 30 minutes, seek

medical attention.

Skin contact: No treatment necessary.

Ingestion: Swallowing small quantities (one teaspoon) will cause no harm to healthy adults. If larger amounts are swallowed, give two glasses of water to drink and seek medical attention.

- 4.2 Most important symptoms and effects both acute and delayed:** Symptoms of accidental over-exposure to high doses of inorganic borate salts have been associated with ingestion or absorption through large areas of severely damaged skin. These may include nausea, vomiting, and diarrhoea, with delayed effects of skin redness and peeling (see Section 11).
- 4.3 Indication of any immediate medical attention and special treatment needed:** Note to physicians: Supportive care only is required for adult ingestion of less than a few grams of the product. For ingestion of larger amounts, maintain fluid and electrolyte balance and maintain adequate kidney function. Gastric lavage is only recommended for heavily exposed, symptomatic patients in whom emesis has not emptied the stomach. Hemodialysis should be reserved for patients with massive acute absorption, especially for patients with compromised renal function. Boron analyses of urine or blood are only useful for verifying exposure and are not useful for evaluating severity of poisoning or as a guide in treatment¹.

Section 5 Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media: Use extinguishing media that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media: None

5.2 Special hazards arising from substance or mixture

None. The product is not flammable, combustible or explosive.

5.3 Advice for fire fighters

Not applicable. The product is itself a flame retardant.

Section 6 Accidental release measures

6.1 Personal precaution, protective equipment and emergency procedures

For non-emergency personnel:

Eye goggles and gloves are not required for normal industrial exposures, but eye protection according to CEN166:1996, Respirators (CEN149) should be considered if environment is excessively dusty.

For emergency responders:

Eye goggles and gloves are not required for normal industrial exposures, but eye protection according to CEN166:1996, Respirators (CEN149) should be considered if environment is excessively dusty.

- 6.2 Environmental precautions:** The product is a water-soluble white powder that may cause damage to trees or vegetation by root absorption. Avoid contamination of water bodies during clean up and disposal. Advise local water authority that none of the affected water should be used for irrigation or for the abstraction of potable water until natural dilution returns the boron value to its normal environmental background level.

6.3 Methods and material for containment and cleaning up

Appropriate containment: Avoid spillage into water and cover drains.

Land spill: Vacuum, shovel or sweep up and place in containers for disposal in accordance with applicable local regulations.

Spillage into water: Where possible, remove any intact containers from the water.

6.4 Reference to other sections

Refer to sections 8, 12 and 13

Section 7 Handling and storage

7.1 Precautions for safe handling

Good housekeeping procedures should be followed to minimise dust generation and accumulation. Avoid spills. Do not eat, drink and smoke in work areas. Wash hands after use. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

No special handling precautions are required, but dry, indoor storage is recommended. To maintain package integrity and to minimise caking of the product, bags should be handled on a first-in first-out basis.

Storage temperature: Ambient
Storage pressure: Atmospheric
Special sensitivity: Moisture (Caking)

7.3 Specific end use(s)

Refer to Annex – Exposure Scenarios.

Section 8 Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values: In the absence of a national OEL, Rio Tinto Borax recommends and applies internally an Occupational Exposure Limit (OEL) of 1 mg B/m³. To convert product into equivalent boron (B) content, multiply by 0.175.

OELs of Member States of the EU

Substance: Boric acid, CAS#: 10043-35-3

Country	8-hr TWA (mg/m ³)	15 min STEL (mg/m ³)	Legal basis
Belgium	2	6	Moniteur Belge no 187, 30-06-2011
Germany	2.6	5.2	TRGS 900 Arbeitsplatzgrenzwerte, 12-01-2012
Italy	2	6	Decree no.106, 3-08-2009
Latvia	10	-	Rules No. 92, 1-02-2011
Lithuania	10	-	Hygiene Norm HN 23:2007; Order No. V-827/A1-287, 15 October 2007
Spain	2	6	Valores Límites Ambientales (VLAs), Table 1, Límites de Exposición Profesional para Agentes Químicos 2011)
Switzerland	10	10	Limit Values at the Workplace 2011, as per SUVA

DNELs

Route of exposure	Workers				Consumers			
	Acute effects local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effects local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not Required				*	0.98 mg/kg/day	*	0.98 mg/kg/day
Inhalation	*	*	*	8.28 mg/m ³	*	*	*	4.15 mg/m ³
Dermal	*	*	*	392.0 mg/kg/day	*	*	*	196.0 mg/kg/day

* No hazard identified

Monitoring procedure: *BS EN 14042:2003 Title identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.*

PNECs

Compartment (Environment)	PNEC (added values)
Water, fresh and marine	2.02 mg B/L
Water, intermittent	13.7 mg B/L
Air	No exposure expected
Soil	5.4 mg B/kg dry soil
Sediment	Waived due to lack of partitioning to sediment
STP	10 mg B/L

8.2 Exposure controls

Appropriate engineering controls: Use local exhaust ventilation to keep airborne concentrations of dust below permissible exposure limits.

Personal protection equipment:

Eye and face protection: Eye protection according to CEN166:1996 may be warranted if environment is excessively dusty.
Skin protection: Standard work gloves (cotton, canvas or leather) may be warranted if environment is excessively dusty.
Respiratory protection: Where airborne concentrations are expected to exceed exposure limits, respirators should be used. (CEN149).

Environmental exposure controls:

Limiting releases from site: Where appropriate, material should be recovered and recycled through the process. Spillages of powder or granulated borates should be swept or vacuumed up immediately and placed in containers for disposal in order to prevent unintentional release to the environment. Waste containing borates should be handled as a hazardous waste and removed by licensed operator to an offsite location where it can be incinerated or disposed to a hazardous landfill.

Water Emissions: Storage should be sheltered from precipitation. Avoid spillage into water and cover drains. Removal from water can only be accomplished by very specific treatment technologies including ion exchange resins, reverse osmosis etc. Removal efficiency is dependent upon a number of factors and will vary from 40 to 90%. Much of the technology is currently not appropriate to high volume or mixed waste streams. Boron is not removed in considerable amounts in conventional STP. If sites discharge to a municipal STP the concentration of boron should not exceed the PNEC in the municipal STP.

Air Emissions: Emissions to air can be removed by one or more of the following dust-control measures: electrostatic precipitators, cyclones, fabric or bag filters, membrane filters, ceramic and metal mesh filters, and wet scrubbers.

Section 9 Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:	White, crystalline solid
Odour	Odourless
Odour threshold:	Not applicable: odourless
pH @ 20°C:	6.1 (0.1% solution); 5.1 (1.0% solution); 3.7 (4.7% solution)
Melting point/ Freezing point:	>1000°C
Initial boiling point and boiling range:	Not applicable: melting point >300°C
Flash point:	Not applicable: inorganic substance
Evaporation rate:	Not applicable: non-volatile
Flammability (solid/gas):	Non-flammable (used as a flame retardant)
Upper/lower flammability or explosive limits:	Not applicable: non-flammable
Vapour pressure:	Not applicable: melting point >300°C
Vapour density:	Not applicable: melting point >300°C
Relative density:	1.49 @ 23°C
Solubility(ies):	Water: 49.2 g/L @ 20°C
Partition coefficient; n-octanol/water:	Log P _{ow} = -1.09 @ 22°C
Auto-ignition temperature:	Not applicable: not self-heating
Decomposition temperature:	If heated above 100 °C water is lost and boric acid converts initially to metaboric acid (HBO ₂) and on further heating forms boric oxide (B ₂ O ₃).
Viscosity:	Not applicable: solid substance
Explosive properties:	Not explosive: does not contain chemical groups associated with explosive properties.

Oxidising properties:

Not oxidising: does not contain chemical groups associated with oxidising properties

9.2 Other information**Molecular weight:**

61.8

Formula:H₃BO₃

Section 10 Stability and reactivity

10.1 Reactivity: None known.

10.2 Chemical stability: Under normal ambient temperatures (-40 °C to +40°C), the product is stable product. When heated it loses water, first forming metaboric acid (HBO₂), and on further heating it is converted into boric oxide (B₂O₃).

10.3 Possibility of hazardous reactions: Boric acid is a weak acid that may cause corrosion of base metals. Reaction with strong reducing agents such as metal hydrides or alkali metals will generate hydrogen gas which could create an explosive hazard.

10.4 Conditions to avoid: Avoid contact with strong reducing agents by storing according to good industrial practice.

10.5 Incompatible materials: Strong reducing agents.

10.6 Hazardous decomposition products: None.

Section 11 Toxicological Information

11.1 Information on toxicological effects

a) Acute toxicity

Method: Acute Oral Toxicity Study – OECD Guideline 401

Species: Rat

Dose: 2000 – 5000 mg/kg body weight

Routes of Exposure: Oral

Results: Low acute oral toxicity. The oral LD₅₀ value in male rats is 3,450 mg/kg bw, and in female rats is 4080 mg/kg bw. Based on the available data, the classification criteria are not met.

Method: Acute Dermal Toxicity Study – U.S. EPA FIFRA Guidelines

Species: Rabbit

Dose: 2,000 mg/kg bw

Routes of Exposure: Dermal

Results: Low acute dermal toxicity; LD₅₀ in rabbits is > 2,000 mg/kg of body weight. Poorly absorbed through intact skin. Based on the available data, the classification criteria are not met.

Method: Acute Inhalation Toxicity Study – OECD Guideline 403

Species: Rat

Dose: 2.12 mg/L

Routes of Exposure: Inhalation

Results: Low acute inhalation toxicity; LC₅₀ in rats is > 2.0 mg/l (or g/m³). Based on the available data, the classification criteria are not met.

(b) Skin corrosion / irritation:

Method: Primary Dermal Irritation Study – EPA FIFRA (40 CFR 163)

Species: New Zealand White Rabbit

Dose: 0.5 g moistened with saline

Routes of Exposure: Dermal

Results: No skin irritation. Mean Primary Irritation Score: 0.1. Based on the available data, the classification criteria are not met.

(c) Serious eye damage / irritation:

Method: Eye Irritation Study – similar to OECD Guideline 405

Species: New Zealand White Rabbit

Dose: 0.1 g

Routes of Exposure: Eye

Results: Not irritating, corneal involvement or irritation clearing in 7 days.

Classification: Based on mean scores < 1, and the effects were fully reversible within 7 days, the classification criteria are not met. Many years of occupational exposure indicate no adverse effects on human eye.

(d) Respiratory or skin sensitisation:

Method: Buehler Test – OECD Guideline 406

Species: Guinea Pig

Dose: 0.4 g 95 % w/w/boric acid

Routes of Exposure: Dermal

Results: Not a skin sensitiser. No respiratory sensitisation studies have been conducted. There are no data to suggest that boric acid is a respiratory sensitiser. Based on the available data, the classification criteria are not met.

(e) Germ cell mutagenicity:

Method: Several *in vitro* mutagenicity studies have been carried out on boric acid including gene mutation in mammalian cells, unscheduled DNA synthesis, chromosomal aberration and sister chromatid exchange in mammalian cells.

Species: L5178Y mouse lymphoma, V79 Chinese hamster cells, C3H/10T1/2 cells, hepatocytes, Chinese hamster ovary (CHO cells).

Dose: 1.0 - 10.0 mg/ml (1000-10000ppm) boric acid

Routes of Exposure: *in vitro*

Results: Not mutagenic. Based on the available data, the classification criteria are not met.

(f) Carcinogenicity:

Method: OECD 451 equivalent.

Species: B6C3F1 mice

Dose: 446; 1150 mg boric acid/kg bw/day

Routes of Exposure: Oral feeding study

Results: No evidence of carcinogenicity. Based on the available data, the classification criteria are not met.

(g) Reproductive toxicity:

Method: Three-generation feeding study, similar to OECD 416 Two-Generation Study

Species: Rat

Dose: 0; 34 (5.9); 100 (17.5) and 336 (58.5) mg boric acid (mg B)/kg bw/day

Routes of Exposure: Oral feeding study

Results: NOAEL in rats for effects on fertility in males is 100 mg boric acid/kg bw equivalent to 17.5 mg B/kg bw.

Method: Prenatal Developmental Toxicity Study of Boric Acid – OECD Guideline 414

Species: Rat

Dose: 0; 19 (3.3); 36 (6.3); 55 (9.6); 76 (13.3) and 143 (25) mg boric acid (mg B)/kg bw.

Routes of Exposure: Oral feeding study

Results: NOAEL in rats for developmental effects on the foetus including foetal weight loss and minor skeletal variations is 55 mg boric acid/kg bw or 9.6 mg B/kg.

Classification: Reproductive Toxicity Category 1B (Hazard statement: H360FD: May damage fertility or the unborn child.)

Method: Occupational studies of evaluating sensitive sperm parameters in highly exposed borate workers. Epidemiological studies evaluating high environmental exposures to boron and developmental effects in humans have been conducted.

Species: Human

Dose: A subset of workers was exposed to 125 mg B/day.

Routes of Exposure: Combined oral ingestion and inhalation

Results: No adverse fertility effects in male workers. Epidemiological studies of human developmental effects have shown an absence of effects in exposed borate workers and populations living in areas with high environmental levels of boron.

Summary of evaluation of the CMR properties:

Boric acid is not mutagenic and has been tested in 2 year bioassays to be negative for carcinogenicity. Accordingly a classification for these endpoints for disodium tetraborates is not required under EC Directive 67/548/EEC or under CLP Regulation (EC) No. 1272/2008. A multigeneration study in the rat gave a NOAEL for fertility in males of 17.5 mg B/kg/day. Developmental effects have been observed in laboratory animals, the most sensitive species being the rat with a NOAEL of 9.6 mg B/kg bw/day. Disodium tetraborate is classified under the 1st ATP to CLP as Repr. 1B; H360FD. While boron has been shown to adversely affect male reproduction in laboratory animals, there was no clear evidence of male reproductive effects attributable to boron in studies of highly exposed workers.

(h) STOT-single exposure:

Method: Standard Test Method for Estimating Sensory Irritancy of Airborne Chemicals – ASTM E981-04 (2004)

Species: Mouse

Dose: 221 - 1096 mg boric acid/m³

Routes of Exposure: Inhalation

Results: The highest concentration of boric acid that was achievable with acceptable control of the aerosol concentration was 1096 mg/m³ with a %RD of 19%. The lowest exposure tested of 221 mg/m³ boric acid resulted in a reduced

respiration rate of 9%, graded as no irritation. Based on the available data, the classification criteria are not met.

Method: Sensory irritation in human volunteers

Species: Human

Dose: 2.5, 5, 10 mg boric acid/m³

Routes of Exposure: Inhalation

Results: No irritation from boric acid was observed at exposures up to 10 mg/m³ among male and female human volunteers under controlled laboratory conditions.

(i) STOT-repeated exposure:

Method: Chronic toxicity study of boric acid, similar to OECD 452

Species: Rat

Dose: 0; 33 (5.9); 100 (17.5); 334 (58.5) mg boric acid (B)/kg bw per day (nominal in diet)

Routes of Exposure: oral: feed

Results: A NOAEL of 17.5 mg B/kg bw/day equivalent to 100 mg boric acid/kg bw/day was determined in a chronic feeding study (2 years) in rats and is based on testes effects. Other effects (kidney, haemopoietic system) are regarded only at even higher dose levels. Based on the available data, the classification criteria are not met.

(j) Aspiration hazard: Physical form of solid powder indicates no aspiration hazard potential.

Toxicokinetics

In the blood boric acid is the main species present and is not further metabolised. Boric acid is distributed rapidly and evenly through the body, with concentrations in bone 2 - 3 higher than in other tissues. Boric acid is excreted rapidly, with elimination half-lives of 1 h in the mouse, 3 h in the rat and < 27.8 h in humans, and has low potential for accumulation. Boric acid is mainly excreted in the urine. Absorption of borates via the oral route is nearly 100 %. For the inhalation route also 100 % absorption is assumed as worst case scenario. Dermal absorption through intact skin is very low with a percent dose absorbed < 0.5%.

Information on likely routes of exposure:

Inhalation is the most significant route of exposure in occupational and other settings. Dermal exposure is not usually a concern because product is poorly absorbed through intact skin. Product is *not* intended for ingestion

Symptoms related to the physical, and chemical and toxicological characteristics:

Products are not intended for ingestion. Small amounts (e.g. a teaspoonful) swallowed accidentally are not likely to cause effects. Symptoms of accidental over-exposure to high doses of inorganic borate salts have been associated with ingestion or absorption through large areas of severely damaged skin. These may include nausea, vomiting, and diarrhoea, with delayed effects of skin redness and peeling.

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Human epidemiological studies show no increase in pulmonary disease in occupational populations with chronic exposures to boric acid and sodium borate dust. Human epidemiological studies indicate no effect on fertility in occupational populations with chronic exposures to borate dust and indicate no effect to a general population with high exposures to borates in the environment.

Section 12 Ecological information

12.1 Toxicity

Note that the data values are expressed as boron equivalents. To convert to this product divide the boron equivalent by 0.175. Studies judged to be unreliable or with insufficient information to evaluate are not included.

Freshwater

Chronic studies

Taxonomic Group	Number of Taxa Tested	Range of Endpoint Values (geometric NOEC/EC10)	References
Algal	4	10 mg B/L (<i>Chlorella pyrenoidosa</i>) to 50 mg B/L (<i>Anacystis nidulans</i>)	3, 4
Higher plants	3	4.0 mg B/L (<i>Phragmites australis</i>) to 60 mg B/L (<i>Lemna minor</i>)	5, 6
Invertebrate and protozoan	7	5.7 mg B/L (<i>Daphnia magna</i>) to 32 mg B/L (<i>Chironomus riparius</i>)	7, 8
Fish	6	2.9 mg B/L (<i>Micropterus salmoides</i>) to 17 mg B/L (<i>Carassius auratus</i>)	9
Amphibian	2	29 mg B/L (<i>Rana pipiens</i>) to 41 mg B/L (<i>Bufo fowleri</i>)	9

Results²: Based on the complete data set of 22 species, the HC₅ value of the species sensitivity distribution is 4.05 mg B/L.

Acute studies

Taxonomic Group	Number of Taxa Tested	Range of Endpoint Values (geometric EC/LC50)	References
Algal	2	10 mg B/L (<i>Chlorella pyrenoidosa</i>) to 28 mg B/L (<i>Selenastrum capricornutum</i>)	3, 10
Invertebrate and protozoan	9	113 mg B/L (<i>Ceriodaphnia dubia</i>) to 1376 mg B/L (<i>Chironomus decorus</i>)	11, 12
Fish	7	80 mg B/L (<i>Pimephales promelas</i>) to 627 mg B/L (<i>Onchorhynchus tschawytscha</i>)	11, 13
Amphibian	2	86 mg B/L (<i>Rana pipiens</i>) to 104 mg B/L (<i>Bufo fowleri</i>)	9

Results²: Based on the complete data set from 46 studies with 20 species, the HC₅ value of the species sensitivity distribution is 27.3 mg B/L

Classification: Based on the acute data for freshwater species, this substance is not classified as hazardous to the environment.

Marine and Estuarine Data

Chronic studies

Taxonomic Group	Number of Taxa Tested	Range of Endpoint Values (geometric NOEC/EC10)	References
Algal	19	5 mg B/L (<i>Emiliana huxleyi</i>) to >100 mg B/L (<i>Agmenellum quadruplicatum</i> , <i>Anacystis marina</i> , <i>Thalassiosira pseudonana</i>)	4

Results: No data are available for invertebrate or vertebrate species. The results from the freshwater data set are recommended as applicable to marine and estuarine species.

Acute studies

Taxonomic Group	Number of Taxa Tested	Range of Endpoint Values (geometric EC/LC50)	References
Invertebrate	3	45 mg B/L (<i>Litopenaeus vannamei</i>) to 83 mg B/L (<i>Americamysis bahia</i>)	14, 15
Fish	2	74 mg B/L (<i>Limanda limanda</i>) to 600 mg B/L (<i>Onchorhynchus tschawytscha</i>)	13, 16

No data are available for algal species.

Sediment

Taxonomic Group	Number of Taxa Tested	Range of Endpoint Values (geometric EC/LC50)	References
Invertebrate	1	82.4 mg B/kg sediment dw (<i>Chironomus riparius</i>)	17, 18

Results: Although limited, the data suggest that sediment organisms are within range of toxicity of aquatic organisms. In addition, the substance will not partition to the sediment, so a sediment/water partitioning approach is justified.

Sewage Treatment Plants (STP)

Taxonomic Group	Number of Taxa Tested	Range of Endpoint Values (geometric NOEC/EC10)	References
Activated sludge	NA	>17.5 mg B/L to 100 mg B/L	19

Microbes	3	10 mg B/L (<i>Opercularia bimarginata</i>) to 20 mg B/L (<i>Paramecium caudatum</i>)	20
----------	---	--	----

Terrestrial Data

Chronic studies

Taxonomic Group	Number of Taxa Tested	Range of Endpoint Values (geometric NOEC/EC10)	References
Plant	28	7.2 mg B/kg dw (<i>Zea mays</i>) to 56 mg B/kg dw (<i>Allium cepa</i>)	21, 22
Invertebrates	9	15.4 mg B/kg dw (<i>Folsomia candida</i>) to 87 mg B/kg dw (<i>Caenorhabditis elegans</i>)	23, 24
Soil micro	3	12 mg B/kg dw (nitrogen mineralization and nitrification test) to 420 mg B/kg dw (soil nitrogen transformation test)	25, 26

Results²: Based on the complete data set, the HC₅ value of the species sensitivity distribution is 10.8 mg B/kg dw.

Phytotoxicity: Boron is an essential micronutrient for healthy growth of plants. It can be harmful to boron sensitive plants in higher quantities. Care should be taken to minimise the amount of borate product released to the environment.

12.2 Persistence and Degradability

Biodegradation is not an applicable endpoint since the product is an inorganic substance.

12.3 Bioaccumulative potential

This product will undergo hydrolysis in water to form undissociated boric acid. Boric acid will not biomagnify through the foodchain. Octanol/Water partition coefficient: Log P_{ow} = -0.7570 @ 25°C (based on boric acid)²⁷.

12.4 Mobility in soil

The product is soluble in water and is leachable through normal soil. Adsorption to soils or sediments is insignificant.

12.5 Results of PBT and vPvB assessment

According to Annex XIII of REACH, criteria for the assessment of PBT and vPvB properties do not apply to inorganic substances.

12.6 Other adverse effects

None

Section 13 Disposal considerations**13.1 Waste treatment methods**

This product is classified as toxic to reproduction (Repr. 1B) and falls within scope of Directive 2008/98/EC as hazardous waste (H10). Dispose via a licensed waste disposal contractor.

Product packaging should be recycled where possible.

Local authorities should be consulted about any specific local requirements.

Such product should, if possible, be used for an appropriate application.

Section 14 Transport information

Transport Classification for Road(ADR) / Rail(RID); Inland waterways (ADN); SEA (IMDG); AIR (ICAO/IATA)

14.1 UN Number:	Not Regulated
14.2 UN Proper Shipping Name:	Not Regulated
14.3 Transport hazard class(es):	Not Regulated
14.4 Packing Group:	Not Regulated
14.5 Environmental Hazards:	Not Regulated
14.6 Special precautions for user:	Not Regulated
14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC code:	Not Regulated

Section 15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 2037/2000 - Substances that deplete the ozone layer: Not manufactured with and does not contain any Group I or Group II ozone depleting substances.

Clean Air Act (Montreal Protocol):- Substances that deplete the ozone layer: Not manufactured with and does not contain any Class I or Class II ozone depleting substances.

Regulation (EC) No 689/2008 - Export and Import of Dangerous Chemicals: Not listed.

Regulation (EU) No 109/2012 – REACH Annex XVII: Restricted to professional users. The product is permitted for use in consumer products where it is below the specific concentration limit.

National Regulations: Ensure all national/local regulations are observed.

Chemical inventory listing:

U.S. EPA TSCA Inventory:	10043-35-3
Canadian DSL:	10043-35-3
EINECS:	233-139-2
South Korea KECI:	KE-03499
Japanese METI & ISHL:	(1)-63
China IECSC:	10043-35-3

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out.

Section 16 **Other information**

Revision Details:

Section 1: Product names; Supplier address; Emergency telephone number.

Section 16: Precautionary phrases.

Abbreviations and acronyms:

ATP: Adaption to Technical Progress

CLP: Classification, Labelling and Packaging Regulation (EC) No. 1272/2008

CMR: Carcinogen, Mutagen, Reproductive Toxicant

EC: Effect concentration

HC: Hazard Concentration

LC: Lethal Concentration

LD: Lethal Dose

STOT: Specific Target Organ Toxicity

DNEL: Derived No Effect Level

LOEC: Lowest Observed Effect Concentration

NA: Not applicable.

NOAEL: No observed adverse effect level

NOEC: No Observed Effect Concentration

PNEC: Predicted No Effect Concentration

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent, very Bioaccumulative

TWA: Time Weighted Average

STEL: Short-term exposure limit

STP: Sewage Treatment Plant

References:

1. Litovitz T L, Norman S A, Veltri J C, Annual Report of the American Association of Poison Control Centers Data Collection System. Am. J. Emerg. Med. (1986), 4, 427-458

2. Chemical Safety Report "Boric acid" September 2010, updated 2012 <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>

3. Fernandez et al. (1984) Phytol (Buenos Aires) 44: 125-133.

4. Antia and Cheng (1975) J Fish Res Bd Can 32: 2487-2494.

5. Bergman, Bruchlos, Marks (1995) Tenside Surf Det 32: 229-237.

6. Wang (1986) Environ Poll (Ser B) 11: 1-14.

7. Gersich and Milazzo (1990) Arch. Environ. Contam. Toxicol. 19: 72-76.

8. Hoofman, van Dongelen-Sevenhuijsen and de Haan (2000). Unpublished report no. V99.1146 to Borax Europe

Limited.

9. Dyer (2001) Chemosphere 44: 369-376.
10. Hansveit and Oldersma (2000) Unpublished report no: V99-157 to Borax Europe Limited.
11. Soucek, Dickinson, Major (2010) Unpublished report to REACH Consortium for Borates.
12. Maier and Knight (1991) Arch. Environ. Contam. Toxicol. 20, 282 – 287.
13. Hamilton and Buhl (1990) Arch. Environ. Contam. Toxicol. 19, 366-373.
14. Li, et al. (2007) Aquaculture 278, 175-178.
15. Pillard et al. (2002) Environ Toxicol Chem, 21, 2131-2137.
16. Taylor et al. (1985) Aquat Toxicol, 7, 135-144.
17. Gerke, A (2011a). Unpublished report to REACH Consortium for Borates.
18. Gerke, A (2011b). Unpublished report to REACH Consortium for Borates.
19. Hanstveit and Schoonmade (2000). Unpublished report no.: V99.156 to Borax Europe Limited.
20. Guhl (2000) SÖFW-Journal 126: 17-24.
21. Hosseini et al. (2007) J Plant Nutrition, 30, 773-781.
22. Aquaterra Environmental (1998) Unpublished report to Environment Canada, Environmental Technology Centre.
23. Becker-van Slooten, Campiche, Tarradellas (2003). Unpublished report to Environment Canada, Environmental Technology Centre.
24. Moser and Becker (2009) Unpublished report to REACH Consortium for Borates.
25. Van Laer, Salaets, Smolders (2010) Unpublished report to REACH Consortium for Borates.
26. Förster and Becker (2009) Unpublished report to REACH Consortium for Borates.
27. Cordia et al. (2003) Unpublished report no: PML 2002-C42r to Borax Europe, Ltd.

For general information on the toxicology of borates see ECETOC Technical Report No. 63 (1995); Patty's Toxicology, 6th Edition Vol. I, (2012) Chap. 23, 'Boron'. Culver, BD & Hubbard SA (1995) Inorganic Boron Health Effects in Humans: An Aid to Risk Assessment and Clinical Judgment. Trace Elements in Experimental Medicine 9(4):175-184.

Full text of Hazard statements mentioned in sections 2 and 3:

H360FD: May damage fertility. May damage the unborn child.

Full text of Risk Phrases mentioned in sections 2 and 3:

R60 May impair fertility.

R61 May cause harm to the unborn child.

Precautionary statements:

P202: Do not handle until all safety precautions have been read and understood.

P281: Use personal protective equipment as required.

P308+P313: IF exposed or concerned: Get medical advice.

P501: Dispose of contents/container in accordance with local regulation.

Precautionary Phrases:

Restricted to professional users.

Do not ingest.

Keep out of reach of children.

Refer to safety data sheet.

Not for use in food or pesticides.

The table in Annex – Exposure Scenarios lists the uses identified and registered for this substance with the indication of the Exposure Scenario(s) that is relevant to each identified use.

Disclaimer:

Borax Europe Limited provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose.

BORAX EUROPE LIMITED MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY BORAX EUROPE LIMITED WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OR RELIANCE UPON THIS INFORMATION.

The following table lists the uses identified and registered for this substance. Each use has a number of applicable human health, environmental and consumer exposure scenarios. These can be found at www.borax.com/EU-REACH/exposure-scenarios

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
1	Production and Import	Production and Import	X						1,7,8,9a,9b,12,14,15,17,18,19,20,21,23,24,25,26,29,30,32,37,38,39	1, 2, 3, 4, 8a, 8b, 9, 14, 15	-	1, 6a	E1 - Importing, manufacture, refining and packaging of borates	ES3 - Refining and processing of borates ES14 - Loading of road tankers ES15 - Off-loading borates from ships ES19 - Packaging into bags (25-50kg) ES20 - Packaging into big bags (750-1500kg) ES21 - General maintenance activities ES32 - Working in a laboratory ES41 - Working in a warehouse
2	Abrasives	Formulation of borates in abrasives		X				3	UCN S351000	3, 4, 5, 8b, 9	4	3	E8 - Generic formulation of borates into materials	ES2 - Closed or largely closed production at high temperatures ES7 - Discharging bags (25 -50 kg) into mixing vessels ES8 - Discharging big bags (750-1500kg) into mixing vessels ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities ES21 - General maintenance activities ES22 - Transfer of substances into small containers ES31 - Compaction and tableting of borate-containing powders ES32 - Working in a laboratory
3	Abrasives	Industrial use of abrasives			X		3, 15, 17	UCN S351000	24		4	4	E9 - Generic industrial use of borates as processing aids in processes and products	ES39 - Industrial and professional use of abrasives
4	Abrasives	Professional use of abrasives			X		X	22	UCN S351000	24		4	10b, 11b	E28 - Generic wide dispersive use of articles containing borates with high release ES39 - Industrial and professional use of abrasives
5	Abrasives	Consumer use of abrasives				X	X	21	UCN S351000	-		4	10b, 11b	E28 - Generic wide dispersive use of articles containing borates with high release ES39 - Industrial and professional use of abrasives ES5 - Consumer exposure for the use of cutting wheels

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
6	Adhesives	Formulation of borates in adhesives		X				6a, 6b, 9, 11	1	3, 4, 5, 8a, 8b, 9, 14	-	2	E7 - Formulation into of borates into adhesives	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substance or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES31 - Compaction and tableting of borate-containing powders</p> <p>ES32 - Working in a laboratory</p>
7	Adhesives	Industrial use of adhesives			X		X	3, 6a, 6b, 16, 17, 18, 19	1	2, 4, 5, 7, 8b, 9, 10, 13, 14	-	5	E12 - Industrial use of adhesives containing borate compounds	<p>ES6 - Industrial application of adhesive</p> <p>ES18 - Transfer of substance or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES26 - Professional application of adhesives</p>
8	Adhesives	Consumer use of articles containing adhesives				X	X	21	-	-	8	10a, 11a	E27 - Generic wide dispersive use of articles containing borates with low release	ESC2 - Consumer mouthing of cardboard and oral contact with boron-containing adhesives

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
9	Agriculture	Formulation of borates in fertilizers		X				1, 3	12	2, 3, 4, 5, 8b, 9, 14	-	2	E4 - Generic formulation of borates into mixtures	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES31 - Compaction and tableting of borate-containing powders</p> <p>ES32 - Working in a laboratory</p>
10	Agriculture	Professional use of fertilizers			X			1, 22	12	2, 3, 4, 5, 8a, 8b, 9, 11, 13	-	8a, 8c, 8d, 8f	E24 - Wide dispersive use of fertilizers containing borates	<p>ES5 - Fertigation using boron-containing liquid fertiliser</p> <p>ES10 - Transfer of boron-containing granular fertiliser</p> <p>ES23 - Transfer of boron-containing liquid foliar fertiliser</p> <p>ES27 - Spreading of boron-containing granular fertiliser</p> <p>ES28 - Application of boron-containing liquid foliar fertiliser</p>
11	Agriculture	Consumer use of fertilizers				X		21	19	-	-	8a, 8c, 8d, 8f	E24 - Wide dispersive use of fertilizers containing borates	ESC3 - Consumer use of boron-containing fertiliser

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
12	Analytical reagent	Formulation into analytical reagents		X				3	21	2, 3, 4, 5, 8b, 9, 15, 19	-	2	E4 - Generic formulation of borates into mixtures	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES32 - Working in a laboratory</p>
13	Analytical reagent	Laboratory use of analytical reagent			X			3,22	21	15	-	8a, b, d, e	E22 - Generic environmental exposure scenario for use of borates in laboratories as analytical reagent	ES32 - Working in a laboratory
14	Autocausticizing	Processing aid						3, 6b	20	8b, 9	-	4	E10 - Industrial use of borates for autocausticizing	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p>

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
15	Catalysts	Manufacture of catalysts	X	X				3, 8, 9	UCN P15500	3, 4, 5, 8b	-	1, 3, 6a, 6b	E3 - Industrial use of borates in the production of diboron trioxide-containing catalysts	ES7 - Discharging bags (25 -50 kg) into mixing vessels ES8 - Discharging big bags (750 – 1500kg) into mixing vessels ES16 - Closed production at ambient temperatures ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities ES21 - General maintenance activities ES22 - Transfer of substances into small containers ES31 - Compaction and tableting of borate-containing powders ES32 - Working in a laboratory
16	Catalysts	Polymer production		X				3, 8	32	2	-	1, 6a, 6b	E2 - Generic industrial use of borates resulting in the manufacture of another substance	ES7 - Discharging bags (25 -50 kg) into mixing vessels ES8 - Discharging big bags (750 – 1500kg) into mixing vessels ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities
17	Cellulose insulation	Formulation of cellulose insulation		X				5, 6a, 6b, 19	UCN I15600	1, 2, 3, 4, 8b	4	3	E8 - Generic formulation of borates into materials	ES7 - Discharging bags (25 -50 kg) into mixing vessels ES8 - Discharging big bags (750 – 1500kg) into mixing vessels ES16 - Closed production at ambient temperatures ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities ES21 - General maintenance activities ES32 - Working in a laboratory
18	Cellulose insulation	Professional use of cellulose insulation			X			19,22	I15600	21	4	8c, 8f	E26 - Wide dispersive use of cellulose insulation	ES36 - Professional installation of cellulose insulation

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
19	Cellulose insulation	Service life of cellulose insulation					X	-	-		4	10a, 11a	E27 - Generic wide dispersive use of articles containing borates with low release	-
20	Ceramics	Production of frits	X	X				3, 13, NACE 23.1	19	1, 2, 3, 8b, 22	4	2, 5, 6a	E17 - Industrial use of borates during the manufacture of frits	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES32 - Working in a laboratory</p>
21	Chemical synthesis	Manufacture of new chemicals using borates	X					3, 8, 9	19	2, 3, 4, 5, 8b, 9, 13, 15, 19, 21	-	1, 6a	E2 - Generic industrial use of borates resulting in the manufacture of another substance	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES31 - Compaction and tableting of borate-containing powders</p> <p>ES32 - Working in a laboratory</p>

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
22	Coatings	Formulation of paints and coatings		X				3, 7, 8, 10	9a, 18	1,2, 3, 4, 8a, 8b, 9, 15	--	2	E6 - Formulation of borates into paints and coatings	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES31 - Compaction and tableting of borate-containing powders</p> <p>ES32 - Working in a laboratory</p>
23	Coatings	Industrial use of paints and coatings			X			3, 7	9a, 18	7, 8b, 9, 10, 13	-	5	E13 - Industrial use of paints and coatings containing borate compounds	ES11 - Industrial use of paints and coatings.
24	Coatings	Professional use of paints and coatings			X			22	9a, 18	5, 8a, 8b, 9, 10, 11, 13, 19		8c, 8f	E25 - Wide dispersive use of paints and coatings containing borates	ES25 - Professional use of paints and coatings

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
26	Construction materials	Formulation/use of borates in construction materials (plaster board, wood)		X				3, 13	K35000, 8	4, 5, 8b, 14, 24, 26	4, 11	2, 3, 5	<p>E4 - Generic formulation of borates into mixtures</p> <p>E8 - Generic formulation of borates into materials</p> <p>E11 - Generic industrial use of borates resulting in inclusion into or onto a matrix</p>	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES31 - Compaction and tableting of borate-containing powders</p> <p>ES32 - Working in a laboratory</p>
27	Construction materials	Professional use of construction materials			X		X	22, 19	K35000, 8	21	4	10a, 11a, 12a	<p>E21 – Generic industrial processing of articles with low abrasive techniques</p> <p>E27 - Generic wide dispersive use of articles containing borates with low release</p>	<p>ES37 - Professional installation of plasterboard, board and other products</p>
28	Construction materials	Consumer use of construction materials				X	X	21	0	-	4	10a, 11a	<p>E27 - Generic wide dispersive use of articles containing borates with low release</p>	<p>ESC4 - Consumer use of boron-containing construction materials (other than insulation)</p>
29	Construction materials	Service life of construction materials					X		-	-	4	10a, 11a	<p>E27 - Generic wide dispersive use of articles containing borates with low release</p>	-

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
30	Detergents	Formulation into detergents		X				3, 10	35	2, 3, 4, 5, 8b, 9, 15	-	2	E5 - Formulation of borates into detergents	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production activities at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES31 - Compaction and tableting of borate-containing powders</p> <p>ES32 - Working in a laboratory</p>
31	Detergents	Professional use of detergents			X			22	35	1, 2, 3, 11, 10, 13, 19	-	8a, 8c, 8d, 8f	E23 - Generic wide dispersive use of borates with 100% release to water	ES4 - Use of fabric detergents in industrial or professional settings
32	Detergents	Consumer use of detergents				X		21	35	-	-	8a, 8c, 8d, 8f	E23 - Generic wide dispersive use of borates with 100% release to water	ES1 - Consumer use of boron-containing detergents
33	Glass	Production of glass wool	X	X				3, 13, NACE 23.1	19	1, 2, 3, 8b, 22	4	2, 5, 6a	E14 - Industrial use of borates during the manufacture of glass wool	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES32 - Working in a laboratory</p>

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
34	Glass	Production of high alkali glass	X	X				3, 13, NACE 23.1	19	1, 2, 3, 8b, 22	4	2, 5, 6a	E15 - Industrial use of borates during the manufacture of high alkali glass	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES32 - Working in a laboratory</p>
35	Glass	Production of low alkali glass	X	X				3, 13, NACE 23.1	19	1, 2, 3, 8b, 22	4	2, 5, 6a	E16 - Industrial use of borates during the manufacture of low alkali glass	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES32 - Working in a laboratory</p>
36	Industrial fluids	Formulation of borates into industrial fluids		X				3, 8, 9, 10, 15	20, 24, 25	3, 4, 5, 8b, 9		2	E4 - Generic formulation of borates into mixtures	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES32 - Working in a laboratory</p>

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
37	Industrial fluids	Industrial use of industrial fluids		X	X			3, 15, 17	19, 20, 24, 25	1, 2, 6, 8a, 8b, 9, 10, 13, 16, 17, 18, 19, 20, 21, 22, 23, 24, 26	-	2, 4, 5, 7	<p>E4 - Generic formulation of borates into mixtures</p> <p>E9 - Generic industrial use of borates as processing aids in processes and products</p> <p>E11 - Generic industrial use of borates resulting in inclusion into or onto a matrix</p> <p>E18 - Generic industrial use of borates in closed systems</p>	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES9 - Diluting metal working fluid concentrate with water</p> <p>ES12 - Use of cleaners in industrial or professional settings</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES17 - Make up of treatment baths for galvanising, plating and other surface treatments</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES29 - Galvanising, plating and other surface treatments of metal articles</p> <p>ES32 - Working in a laboratory</p> <p>ES33 - Use of metal working fluids in machining</p> <p>ES34 - Greasing at high energy conditions</p>
38	Industrial fluids	Consumer use of automotive fluids				x		21	4, 16, 24	-	-	9a, 9b	<p>E27 - Generic wide dispersive use of articles containing borates with low release</p>	<p>ESC8 - Consumer exposure for the use of automotive fluids</p>

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
39	Metallurgy	Formulation into alloys	X	X				3, 14	7, 19	8b,22,23, 24	7	1, 2	E2 - Generic industrial use of borates resulting in the manufacture of another substance	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES32 - Working in a laboratory</p>
40	Metallurgy	Manufacture of flux mixtures and pastes	X	X				3, 10, 13	38	3, 4, 5, 8b, 9, 14	-	2	E4 - Generic formulation of borates into mixtures	<p>ES2 - Closed or largely closed production at high temperatures</p> <p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production activities at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES32 - Working in a laboratory</p>

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
41	Metallurgy	Industrial use of fluxes for (Precious) Metal smelting			X			3, 14	7, 19	22	7	6b	E2 - Generic industrial use of borates resulting in the manufacture of another substance	ES2 - Closed or largely closed production at high temperatures ES7 - Discharging bags (25 -50 kg) into mixing vessels ES8 - Discharging big bags (750 – 1500kg) into mixing vessels ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities ES21 - General maintenance activities ES32 - Working in a laboratory
42	Metallurgy	Industrial use of flux pastes for coating brazing and welding rods			X			3,10	38	14	7	5	E11 - Generic industrial use of borates resulting in inclusion into or onto a matrix	ES24 - Industrial use of flux pastes to coat welding/brazing rods
43	Metallurgy	Industrial/Professional Use of welding, brazing or soldering rods			X			3, 14, 15, 17, 19	38	13, 25, 26	-	4	E9 - Generic industrial use of borates as processing aids in processes and products	ES40 - Industrial and professional use of fluxes in welding/brazing
44	Metallurgy	Use of borates in metal treatment (plating, passivation, galvanising etc)			X			3, 15, 17	14	3,4,5, 8a, 8b	-	4	E9 - Generic industrial use of borates as processing aids in processes and products	ES17 - Make up of treatment baths for galvanising, plating and other surface treatments ES29 - Galvanising, plating and other surface treatments of metal articles
45	Non Oxide Ceramics	Intermediate use in the production of non oxide ceramic powders			X			8,9,13	19	3,4 8b 22,23,24	4	1, 2, 5, 6a, 6b	E2 - Generic industrial use of borates resulting in the manufacture of another substance E4 - Generic formulation of borates into mixtures E11 - Generic industrial use of borates resulting in inclusion into or onto a matrix	ES2 - Closed or largely closed production at high temperatures ES8 - Discharging big bags (750 – 1500kg) into mixing vessels ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities ES38 - Crushing grinding borate-containing powders

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
46	Nuclear applications	Industrial use of borates in closed nuclear system			X			23	37	1, 2, 8b	-	7	<p>E19 - Industrial use of borates in nuclear power plants with release to water</p> <p>E20 - Industrial use of borates in nuclear power plants without release to water</p>	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES32 - Working in a laboratory</p>
47	Oil industry	Formulation into cement		X				2b	K35100	2, 3, 8b	-	2	<p>E4 - Generic formulation of borates into mixtures</p>	<p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES32 - Working in a laboratory</p>
48	Oil industry	Industrial use of cement			X			2b	K35100	8b, 4	-	5	<p>E11 - Generic industrial use of borates resulting in inclusion into or onto a matrix</p>	<p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES32 - Working in a laboratory</p>
49	Photography	Formulation into photographic solutions		X				3, 10	20 30	4, 5, 8b, 9	-	2	<p>E4 - Generic formulation of borates into mixtures</p>	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES22 - Transfer of substances into small containers</p>
50	Photography	Industrial use of photographic solutions			X			3	30	19	-	4	<p>E9 - Generic industrial use of borates as processing aids in processes and products</p>	<p>ES35 - Make up of stock solution for photographic applications</p>

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
51	Photography	Professional use of photographic solutions			X			22	30	13, 19	-	8a	E23 - Generic wide dispersive use of borates with 100% release to water	ES30 - Use of developer and fixer solutions ES35 - Make up of stock solution for photographic applications
53	Printing paper	Formulation of borate PVA solutions		X				3, 10	20	4, 5, 8b	-	1, 6a, 6b	E2 - Generic industrial use of borates resulting in the manufacture of another substance	ES7 - Discharging bags (25 -50 kg) into mixing vessels ES8 - Discharging big bags (750 – 1500kg) into mixing vessels
54	Refractories	Formulation in refractory mixtures		X				3, 15, 10	0	1, 2, 3,4, 5, 8a, 9, 21, 22, 23, 24,	4	2,3	E4 - Generic formulation of borates into mixtures E8 - Generic formulation of borates into materials	ES7 - Discharging bags (25 -50 kg) into mixing vessels ES8 - Discharging big bags (750 – 1500kg) into mixing vessels ES13 - Preparing and applying refractory mixes ES16 - Closed production at ambient temperatures ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities ES21 - General maintenance activities ES31 - Compaction and tableting of borate-containing powders ES22 - Transfer of substances into small containers ES32 - Working in a laboratory
55	Refractories	Industrial use of refractories mixtures			X		X	3, 14	15	7,14,19		5	E11 - Generic industrial use of borates resulting in inclusion into or onto a matrix	ES13 - Preparing and applying refractory mixes

IU number	Sector	Identified Use	Life cycle stage					Sector of use category (SU)	Chemical Product Category (PC)	Process category (PROC)	Article category (AC)	Environmental release category (ERC)	Exposure Scenario	
			Manufacture	Formulation	End use	Consumer use	Service life (for articles)						Environment	Human Health
56	Tablet Production and Use	Swimming pool tablets production		X				3	37	2, 3, 4, 5, 8b, 9, 15, 19	-	5	E11 - Generic industrial use of borates resulting in inclusion into or onto a matrix	<p>ES7 - Discharging bags (25 -50 kg) into mixing vessels</p> <p>ES8 - Discharging big bags (750 – 1500kg) into mixing vessels</p> <p>ES16 - Closed production at ambient temperatures</p> <p>ES18 - Transfer of substances or preparations from/to large vessels/containers at dedicated facilities</p> <p>ES21 - General maintenance activities</p> <p>ES22 - Transfer of substances into small containers</p> <p>ES31 - Compaction and tableting of borate-containing powders</p> <p>ES32 - Working in a laboratory</p>
57	Tablet Production and Use	Swimming pool tablet use			X			22	-	0	-	8a, 8d	E23 - Generic wide dispersive use of borates with 100% release to water	ES1 - Professional use of swimming pool tablets.
58	Toys	Consumer use of modelling clays				x		21	9b	-	-	11a	E27- Generic wide dispersive use of articles containing borates with low release	ESC7 - Consumer use of modelling clays

Note: The IU number as well as the Exposure Scenarios numbering is correct. Even if the numbering might be inconsistent in some cases, this is not a mistake. There are no documents missing.